

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Mixtures
Product name	: PROMASTOP®-M
Type of product	: Solid, dry powder.
Product group	: Fire stopping mortar

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Etex Building Performance N.V.  
Bormstraat 24  
2830 Tiselt - BELGIUM  
T +32 15 71 81 00 - F +32 15 71 81 09  
[info@promat-international.com](mailto:info@promat-international.com) - [www.promat-international.com](http://www.promat-international.com)

#### Other

Siniat S.A.- Le Pin  
3 Route de Claye  
77181 Le Pin - France  
T +33 1 60 26 64 00  
[www.siniat.fr](http://www.siniat.fr)

#### Other

Etex Building Performance Limited  
Gordano House, Marsh Lane, Easton-in-Gordano  
BS20 ONE Bristol - United Kingdom  
T +44 1275 377 773  
[marketinguk@promat.co.uk](mailto:marketinguk@promat.co.uk) - [www.promat.co.uk](http://www.promat.co.uk)

#### Other

Promat s.r.o.  
Kkalova 22/784  
16000 Praha 6 - Bubenec - Czech Republic  
T +420 224 390 811 - F +420 233 333 576  
[promat@promatpraha.cz](mailto:promat@promatpraha.cz) - [www.promatpraha.cz](http://www.promatpraha.cz)

#### Other

Etex Building Performance, Etex Nordic A/S  
Kometvej 36  
6230 Rodekro - Denmark  
T +45 7366 1999  
[info@promat.nu](mailto:info@promat.nu) - [www.promat.nu](http://www.promat.nu)

#### Other

Promat GmbH  
Scheifenkamp 16  
40878 Ratingen - Germany  
T +49-2102 493 0 - F +49-2102 493 111  
[mail@promat.de](mailto:mail@promat.de) - [www.promat.de](http://www.promat.de)

#### Other

Promat d.o.o.  
Trata 50  
4220 Skofja Loka - Slovenia  
T +386 4 51 51 451 - F +386 4 51 51 450  
[info@promat-see.com](mailto:info@promat-see.com) - [www.promat-see.com](http://www.promat-see.com)

#### Other

Promat AG  
Stationsstrasse 1  
8545 Rickenbach Sulz - Switzerland  
T +41 52 320 9400 - F +41 52 320 9402  
[office@promat.ch](mailto:office@promat.ch) - [www.promat.ch](http://www.promat.ch)

#### Other

Promat Fire Protection LLC  
Plot No. 597-921 Dubai Investment Park 2  
123945 Dubai - United Arab Emirates

#### Other

Promat UK Ltd.(Carlton Factory)  
Lawn Road Industrial Estate  
S81 9LB Carlton in Lindrick Workshop - United Kingdom  
T +441909731757 - F +441909733992  
[salesuk@promat.co.uk](mailto:salesuk@promat.co.uk) - [www.promat.co.uk](http://www.promat.co.uk)

#### Other

Etex Building Performance S.p.A.  
Via Perlasca 14  
27010 Vellezzo Bellini (PV) - Italy  
T +39 0382 4575 245 - F +39 0382 4575 250  
[info@promat.it](mailto:info@promat.it) - [www.promat.it](http://www.promat.it)

#### Other

Promat TOP Sp. z.o.o.  
ul. Przeclawska 8  
03-879 Warszawa - Poland  
T +48-22 212 2280 - F +48-22 212 2290  
[top@promatop.pl](mailto:top@promatop.pl) - [www.promatop.pl](http://www.promatop.pl)

#### Other

Promat France  
2 rue Charles-Edouard JEANNERET- CS 90129  
78306 POISSY Cedex - France  
T +33 1 39 79 61 60  
[info@promat.fr](mailto:info@promat.fr) - [www.promat.fr](http://www.promat.fr)

#### Other

Promat Ibérica S.A.  
C/ Velazquez, 47 – 6° Izquierda  
28001 Madrid - Spain  
T +34 91 781 1550 - F +34 91 575 15 97  
[info@promat.es](mailto:info@promat.es) - [www.promat.es](http://www.promat.es)

#### Other

Etex Building Performance GmbH  
St.-Peter-Straße 25  
4021 Linz - Austria  
T +43 732-6912-0  
[info.at@etexgroup.com](mailto:info.at@etexgroup.com) - [www.promat.at](http://www.promat.at)

#### Other

Promat B.V.  
Vleugelboot 22  
3991 CL Houten - Nederland  
T +31 30 241 0770 - F +31 30 241 0771  
[info@promat.nl](mailto:info@promat.nl) - [www.promat.nl](http://www.promat.nl)

#### Other

A + B (Promat Russia)  
ul. Vernadskogo 84/2  
119/606 Moscow - Russia  
T +7 (495) 246-0101 - F +7 (495) 246-0192  
[sales@promat.ru](mailto:sales@promat.ru) - [www.promat.ru](http://www.promat.ru)

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

T +971 4 885 3070 - F +971 4 885 3588  
[info@promatfp.ae](mailto:info@promatfp.ae) - [www.promatmiddleeast.com](http://www.promatmiddleeast.com)

### 1.4. Emergency telephone number

Emergency number : +32 15 71 81 00  
During office hours:  
Monday-Friday: 8.00 a.m. - 4.30 p.m. (MEZ) .  
Language  
English  
French  
Dutch

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 1 H318  
Skin sensitisation, Category 1 H317  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger  
Hazardous ingredients : Portland cement  
Hazard statements (CLP) : H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.  
Precautionary statements (CLP) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 - IF ON SKIN: Wash with plenty of water and soap.  
P261 - Avoid breathing dust.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P501 - Dispose of contents/container to an approved waste disposal plant  
Extra phrases : Skin contact with wet cement, fresh concrete or mortar may cause irritation, dermatitis or burns.  
May cause damage to products made of aluminium or other non-noble metals.

### 2.3. Other hazards

Other hazards not contributing to the classification : Depending upon the source of the Portland cement, the product could be contaminated with chromium VI. - In several countries, the soluble chromium VI is legally limited to 0.0002% of the total dry weight. If soluble chromium VI is present in the Portland cement above the

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

0.0002%, a reduction agent has been added to it to keep the content of soluble chromium VI under the 0,0002%. The activity of this reduction agent is limited in time, what limits the shelf life of the product. The product should be used within 1 year after its production date. Natural contamination of some substances of the preparation with crystalline silica could occur. The inhalation of quartz containing dust, in particular the fine dust fraction (respirable size), in high concentrations or over repeated or prolonged periods of time can be hazardous to health and may lead to chronic lung disease and an increased risk of lung cancer. This risk will be minimal if correct working practices are observed and applied. (Refer to Section 8). According to the International Agency for Research on Cancer (IARC Monograph Volume 100C - 2012) "Crystalline silica inhaled in the form of quartz or cristobalite is carcinogenic to humans (Group 1).".

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Portland cement	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4 (REACH-no) 02-2119682167-31	2 - 70	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Fly ashes	(CAS-No.) 68131-74-8 (EC-No.) 268-627-4 (REACH-no) 01-2119491179-27	0 - 30	Eye Irrit. 2, H319
Flue dust Portland cement	(CAS-No.) 68475-76-3 (EC-No.) 270-659-9 (REACH-no) 01-2119486767-17	0 - 10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Crystalline Silica, respirable fraction substance with a Community workplace exposure limit	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	< 1	STOT RE 1, H372

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Crystalline Silica, respirable fraction	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	( 1 < C < 10) STOT RE 2, H373 ( C >= 10) STOT RE 1, H372

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: In case of allergy, inflammation or irritation, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Rinse throat with water and blow nose to evacuate dust. If nose or airways become inflamed, seek medical advice.
First-aid measures after skin contact	: Remove all dust as much as possible. Take off contaminated clothing. Immediately rinse with plenty of water. If skin irritation occurs: Get medical advice/attention. In case of allergy, seek medical advice.
First-aid measures after eye contact	: Do not rub the eye. Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Cement dust may irritate the throat and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of occupational exposure limits.
Symptoms/effects after skin contact	: When moistened by water or sweat, the Portland cement component may lead to skin inflammation, contact dermatitis or even delayed onset burns due to high alkalinity. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Risk of serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media can be used.

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire : Product is not explosive. The product is non-combustible.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO<sub>2</sub>).

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid dust formation. Avoid breathing dusts. Avoid eye and skin contact. See sections 7 and 8.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Dampen down any dust or use vacuum cleaner with correct filter.  
Measures in case of dust release : Prevent spread of dust.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not allow product to spread into the environment. Do not allow entry to drains, sewers, water courses or soil.

### 6.3. Methods and material for containment and cleaning up

For containment : Use closed containers to avoid dust release.  
Methods for cleaning up : Minimize generation of dust. Do not use compressed air for cleaning. Do not dry sweep. Dampen down any dust or use vacuum cleaner with correct filter.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

See sections 7, 8 and 11.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid dust formation. Do not breathe dust. Avoid contact with skin and eyes. Ensure prompt removal from eyes, skin and clothing. Wear personal protective equipment. Use always respiratory protective equipment when exposures are likely or can be foreseen to exceed the Occupational Exposure Limits or Workplace Exposure Limits in UK (refer to local regulations).  
Handling temperature : 5 - 45 °C  
Hygiene measures : Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in dry, covered and frost proof area. Protect from moisture. Keep away from food, drink and animal feeding stuffs.  
Incompatible materials : Avoid contact with aluminium.  
Maximum storage period : 12 months The packaging is marked with the packing date, the storage conditions and the storage period appropriate to maintain the activity of the reducing agent and to keep the content of soluble chromium VI below the limit indicated in section 2.  
Storage temperature : 5 - 45 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Portland cement (65997-15-1)		
Ireland	Local name	Cement(Portland)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> 4 mg/m <sup>3</sup>
United Kingdom	Local name	Portland cement
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable dust 4 mg/m <sup>3</sup> respirable dust

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Potassium Aluminium Silicate (12001-26-2)		
Ireland	Local name	Mica
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> total inhalable dust 0,8 mg/m <sup>3</sup> respirable dust
United Kingdom	Local name	Mica
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	0,8 mg/m <sup>3</sup> respirable 10 mg/m <sup>3</sup> total inhalable
Cellulose (9004-34-6)		
Ireland	Local name	Cellulose
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> 4 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
United Kingdom	Local name	Cellulose
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable dust 4 mg/m <sup>3</sup> respirable
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> inhalable dust
Crystalline Silica, respirable fraction (14808-60-7)		
EU	Local name	Silica crystalline (Quartz)
EU	Notes	SCOEL Recommendations (2003)
Ireland	Local name	Quartz, respirable dust, (see Silica, crystalline)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	0,1 mg/m <sup>3</sup>
United Kingdom	Local name	Silica
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	0,1 mg/m <sup>3</sup> respirable crystalline

Occupational Exposure Limits / Workplace Exposure Limits for particles not otherwise classified or regulated (nuisance dust) : - in UK: Inhalable: 10 mg/m<sup>3</sup>. Respirable: 4 mg/m<sup>3</sup>  
- in Ireland: Inhalable: 10 mg/m<sup>3</sup>. Respirable: 4 mg/m<sup>3</sup>

Additional information : Ensure all national/local regulations are observed.

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide appropriate exhaust ventilation at places of dust forming.

#### Hand protection:

Use alkali resistant gloves.

#### Eye protection:

Safety glasses with side shields. Use splash goggles when eye contact due to splashing is possible. Foresee eye cleaning on the workplace.

#### Skin and body protection:

Use loose work clothes with closed sleeves. Preventive skin protection creams can be used, but not after skin contact with the product.

#### Respiratory protection:

Use appropriate respiratory equipment when exposures are likely or can be foreseen to exceed the Occupational Exposure Limits or Workplace Exposure Limits for the UK (e.g. for exposures up to 10 times the OEL (WEL) use at least a P2 type duct mask. For higher exposure, use a P3 type mask).



#### Environmental exposure controls:

Avoid release to the environment. Do not allow to enter drains or water courses.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Solid  
Appearance : Powder.  
Colour : Grey.  
Odour : No data available

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold	: No data available
pH	: 11 - 13,5 (in aqueous solution).
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Reacts alkaline with water. A proposed reaction takes place in contact with water, during which the product hardens and forms a solid mass, which does not react with the environment.

### 10.2. Chemical stability

Stable under normal conditions. Shelf life is maximum 12 months.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Humidity during storage.

### 10.5. Incompatible materials

Reacts exothermically with acids. The wet product is alkaline and reacts with acids, ammonium salts and base metals e.g. aluminum, zinc or brass. The reaction with base metals produces hydrogen.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Portland cement (65997-15-1)</b>	
LD50 oral	> 2000 mg/kg mouse
LD50 dermal rabbit	> 2000 mg/kg LD0 : 2000 mg/kg
<b>Flue dust Portland cement (68475-76-3)</b>	
LD50 oral rat	> 1848 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 6,04 g/m <sup>3</sup>

Skin corrosion/irritation	: Cement powder or a mixture of cement with water can cause irritant contact dermatitis, and/or delayed onset of skin burns. These burns can be very serious in prolonged contact with skin. pH: 11 - 13,5 (in aqueous solution).
Serious eye damage/irritation	: Causes serious eye damage. pH: 11 - 13,5 (in aqueous solution).
Respiratory or skin sensitisation	: May cause an allergic skin reaction.

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information	: May cause sensitisation of susceptible persons by skin contact
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Inhaling cement dust may aggravate existing respiratory system disease(s) and/or medical conditions such as emphysema or asthma and/or existing skin and/or eye conditions.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation. The fibres used in this product do not meet the definition of critical or respirable fibre as defined by WHO convention because of their large diameter. Because the fibres are considered as non-respirable, they are not expected to pose a cancer risk.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Flue dust Portland cement (68475-76-3)	
EC50 Daphnia 1	100 mg/l
ErC50 (algae)	22,4 mg/l
NOEC chronic crustacea	50 mg/l

#### 12.2. Persistence and degradability

PROMASTOP®-M	
Persistence and degradability	Not readily biodegradable.

#### 12.3. Bioaccumulative potential

PROMASTOP®-M	
Bioaccumulative potential	Not expected to bioaccumulate.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Additional information : Accidental spillage of cement powder in waste water, results in a low increase in the pH. Hydrated cement is a stable material that definitely sets its compounds and makes them insoluble.. Do not allow entry to drains, sewers, water courses or soil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : In case of disposal, harden with water. Dispose the hardened product as concrete waste.  
European List of Waste (LoW) code : 10 13 14 - waste concrete and concrete sludge  
16 03 03\* - inorganic wastes containing dangerous substances  
17 01 01 - concrete  
17 09 04 - mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03  
15 01 01 - paper and cardboard packaging

### SECTION 14: Transport information

In accordance with ADN / ADR / IATA / IMDG / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Not regulated

#### - Transport by sea

Not regulated

#### - Air transport

Not regulated

#### - Inland waterway transport

Not regulated

#### - Rail transport

Not regulated

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

47. Chromium VI compounds	PROMASTOP®-M
---------------------------	--------------

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations

: REGULATION (EC) n° 1907/2006 - REACH - Annex XVII, RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES, 47:  
1.- Cement and cement-containing preparations shall not be used or placed on the market, if they contain, when hydrated, more than 0,0002 % soluble chromium VI of the total dry weight of the cement.  
2.- If reducing agents are used the packaging of cement or cement-containing preparations shall be legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Indication of changes:

1. Identification of the substance/mixture and of the company/undertaking. 2. Hazards identification. 3.2. Mixtures. 7. Handling and storage. 8. Exposure controls/personal protection. 11. Toxicological information. 15. Regulatory information. 16. Other information.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
------------	---



# PROMASTOP®-M

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet applicable for regions : CY;GB;GI;IE;IS;MT

SDS EU (REACH Annex II)

*The Safety Information given in this document was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This Safety Information was prepared and is to be used only for this product. If the product is used as a component in another product, this Safety Information may not be applicable.*

*This data sheet and the information it contains is not intended to supersede any terms or conditions of sale and does not constitute a specification. Nothing contained herein is to be construed as a recommendation for use in violation of any patent or applicable laws or regulations.*